



3 ~ 4 hours
Recommended Solution

0 ~ 35°C
Recommended Operating
Ambient Temperature

BOS-B80 Pro-A3-Cabinet

BOS-B80 Pro-A3-Cabinet



Durable & Long-Lasting

IP55 waterproof and C4 corrosion resistant, built to last over 10 years



Flexible

Standard prefabricated cabinet for flexible on-demand deployment, suitable for multiple application scenarios



Environmentally Friendly

Free of heavy metals and non-polluting to the environment

Model		BOS-B80 Pro-A3-Cabinet
IP Rating of Enclosure		IP55
Bearing Capacity		Max.580kg
Weight Approximate		≈136kg
Dimension (W×D×H)		835×940×1290
Altitude		≤3000m
Recommended Operating Temperature ^[1]		Charge : 0 ~ 55°C; Discharge : -20 ~ 55°C
Warranty		10 years
Color		White (RAL9016)
Material		SGCC
Applicable to the Product ^[2]		BOS-B Pro-A3

[1] Recommended System Operating Conditions: 0.25C Charging & Discharging, 25°C, 90% DOD, 70%EOL;
Recommended Environmental Conditions: Outdoor open air installation; avoid areas with strong corrosive gas, heavy salt spray, severe vibration and flood prone locations.

[2] Accommodates max. 1×BOS-B-PDU-2-A + 4×BOS-B-Pack16-A3